



Kane Mailing Systems Ltd, Glamorgan House,
Ystrad Mynach, Hengoed, CF82 7AN

Page 1of2

TEL: (01443 813588
FAX: (01443) 813587

EEmail info@kanemailing.com

Contact Kane Now
FREEPHONE 0800 216551

Secap DP125i



How will your business benefit

- **Future-proof mailing** – **intellilink** connects the **Secaps DP 125i** to a secure server, via the Internet enabling services such as postal tariff changes, software updates and advertising slogans to be downloaded quickly and effortlessly.
- **Correct value postage** – every letter , every time – the **DP125i** incorporates a 2.5kg integral weighing platform, freeing up desk space and guaranteeing that each letter or package bears the correct postage value.
- **Fast, accurate postage re-crediting** – Replenish your meter 24 hours a day with simple one touch refills via POSTAGE-PHONE, quick secure and hassle free.
- **Easy to use** - all controls are fully integrated on one clear control panel with user friendly instructions to guide the operator through each stage of processing mail.
- **Streamlined processing** - efficiently frank and seal mail pieces up to 9.5mm thick, whilst larger mail is quickly processed with self adhesive tape strips. Mailing couldn't be simpler with up to 5 presets for your most commonly used jobs.
- **Monitor postal spend** – control postage costs with tracking and reporting for up to 25 named departmental or client accounts.
- **Strengthen your brand** – enhance standard envelopes into eye-catching branded mail pieces with tailor made customised logos.
- **Track incoming mail** – date and time stamping incoming post ensures ail is handled efficiently.



Kane Mailing Systems Ltd, Glamorgan House,
Ystrad Mynach, Hengoed, CF82 7AN

Page 2of2

TEL: (01443) 813588
FAX: (01443) 813587

E-Mail info@kanemailing.com

Contact Kane Now
FREEPHONE 0800 216551

Secap DP125i specifications

Physical dimensions

Length	345mm
Depth	400mm
Height	230mm
Weight	6.8kg approx

Speed

Up to 30 letters per minute

Material sizes

Minimum material size	76mm x 127mm
Maximum material size	330mm x 381mm
Material thickness	9.5mm (max) to 0.18mm (min)
Envelope flap depth for sealing	76mm(max) to 22mm (min)

Operating features

- Slogan and town circle download (by modem)
- 2.5kg integrated weighing platform
- Auto-dating
- Water level indicator
- Seal only/no seal modes
- Low postage warning
- High value protection
- Original value resetting
- Low ink warning
- Password security
- PC interface
- 5 job presets
- Up to 25 accounts

Electrical

10-240v, 50/60 Hz 3A

Noise

55dB

Connectivity requirements

Connects to a standard analog phone line